

Explosion Proof Switches



Safety Switches with positively operated ATEX EExd IIC T6 certified explosion proof contact blocks.
For use in Zone 1 applications.

Switches are available in Stainless Steel with choice of 1NC 1NO, 2NC, 3NC 1NO, or 2NC 2NO blocks.

Harmonised European Standards:
EN 50014 : 1997
EN 50018 : 2000



KM-Ex



KP-Ex



GLES-Ex



GLES-SS-Ex



GLS-Ex



GLS-SS-Ex



GLHL-SS-Ex



GLHD-SS-Ex



GLHL-Ex



GLHD-Ex



GLHR-Ex

Sales Number	Type	Pre-wired cables	Contacts
200016	Kobra KP-Ex	1 x 3m. 4 core	1NC 1NO
200019	Kobra KP-Ex	1 x 3m. 4 core	2NC
203016	Kobra KM-Ex	1 x 3m. 4 core	1NC 1NO
203019	Kobra KM-Ex	1 x 3m. 4 core	2NC
146003	GLES-Ex	1 x 3m. 4 core	1NC 1NO
146004	GLES-Ex	2 x 3m. 4 core	3NC 1NO
146005	GLES-Ex	1 x 3m. 4 core	2NC
146006	GLES-Ex	2 x 3m. 4 core	2NC 2NO
147003	GLES-SS-Ex	1 x 3m. 4 core	1NC 1NO
147004	GLES-SS-Ex	2 x 3m. 4 core	3NC 1NO
147005	GLES-SS-Ex	1 x 3m. 4 core	2NC
147006	GLES-SS-Ex	2 x 3m. 4 core	2NC 2NO
142025	GLS-Ex	1 x 3m. 4 core	1NC 1NO
142028	GLS-Ex	1 x 3m. 4 core	2NC
144025	GLS-SS-Ex	1 x 3m. 4 core	1NC 1NO
144026	GLS-SS-Ex	1 x 3m. 4 core	2NC
141003	GLHD-Ex	1 x 3m. 4 core	1NC 1NO
141014	GLHD-Ex	2 x 3m. 4 core	3NC 1NO
141017	GLHD-Ex	1 x 3m. 4 core	2NC
141018	GLHD-Ex	2 x 3m. 4 core	2NC 2NO
141007	GLHL-Ex	1 x 3m. 4 core	1NC 1NO
141015	GLHL-Ex	2 x 3m. 4 core	3NC 1NO
141019	GLHL-Ex	1 x 3m. 4 core	2NC
141020	GLHL-Ex	2 x 3m. 4 core	2NC 2NO
141011	GLHR-Ex	1 x 3m. 4 core	1NC 1NO
141016	GLHR-Ex	2 x 3m. 4 core	3NC 1NO
141021	GLHR-Ex	1 x 3m. 4 core	2NC
141022	GLHR-Ex	2 x 3m. 4 core	2NC 2NO
145003	GLHD-SS-Ex	1 x 3m. 4 core	1NC 1NO
145014	GLHD-SS-Ex	2 x 3m. 4 core	3NC 1NO
145017	GLHD-SS-Ex	1 x 3m. 4 core	2NC
145018	GLHD-SS-Ex	2 x 3m. 4 core	2NC 2NO
145007	GLHL-SS-Ex	1 x 3m. 4 core	1NC 1NO
145015	GLHL-SS-Ex	2 x 3m. 4 core	3NC 1NO
145019	GLHL-SS-Ex	1 x 3m. 4 core	2NC
145020	GLHL-SS-Ex	2 x 3m. 4 core	2NC 2NO
145011	GLHR-SS-Ex	1 x 3m. 4 core	1NC 1NO
145016	GLHR-SS-Ex	2 x 3m. 4 core	3NC 1NO
145021	GLHR-SS-Ex	1 x 3m. 4 core	2NC
145022	GLHR-SS-Ex	2 x 3m. 4 core	2NC 2NO

Other cable lengths available upon request

Classification EEx d IIC T6
PTB 00 ATEX 1093X
IBExU 01 ATEX 1007X
Rated Voltage 250V a.c.
Rated Current 4A a.c.
Cable length 3m